



Display	VT575CE	VT585CE	VT595CE
Type	Graphic 256 color STN	Graphic 65k color TFT	
Touch Screen	Analog		
Backlighting	CCFL		
Min. lamp life at 25°C (h)	15.000	30.000	50.000
Resolution pixels h-v (inches)	640x480 (7,5")	640x480 (10,4")	800x600 (12,1")

Processor	
CPU	VIA Eden 400Mhz

System memory	
System RAM (bytes)	128M
Resident flash array (bytes)	64M

Interfaces	
MSP serial port (VTxxxCE 1x100)	RS232/422/485/TTY 20 mA
ASP serial port (VTxxxCE 1x100)	RS232/485
Standard serial port	RS232
Parallel port	Bidirectional
USB port	v. 1.1
Mouse PS/2 port	1
Keyboard PS/2 port	1
CardBus slots (for Compact Flash)	1
PCI slots (VTxxxCE 0x100)	1

Networks	
Integrated (in all models)	Ethernet 10/100 Mbit - Rj45

Dimensions			
External (W x H x D) (mm)	245,9x188,6x93	336,3x256x93	336,3x256x93
Cut-out (W x H) (mm)	233x176	314x240	314x240

Clock	
Hardware clock	With battery

Technical data	
Power supply	18...32 Vcc
Power consumed (24 Vdc)	~ 25 W
Protection level	IP 65 front
Operating temperature (°C)	0...+50
Storage/transport temperature (°C)	-20...+65
Humidity (non condensing)	85%
Weight (kg)	~ 3,8
Certificates of approval	CE

Installed Software	
Operating System	Microsoft® Windows® CE 4.2 .NET English