

Display	XS585	XS595	XS615
Type	Graphic LCD 65k color TFT		
Touch Screen	Analog		
Backlighting	CCFL		
Min. lamp life at 25°C (h)	30.000	30.000	50.000
Resolution pixels h-v (inches)	640x480 (10,4")	800x600 (12,1")	1024x768 (15")

Processor		
CPU	Intel® Celeron® 400, 650 MHz	Intel® Celeron® M 600 MHz - Pentium® M 1.1/1.6 GHz

System memory		
System RAM (bytes)	128 - 256 - 512 M	256 - 512 M
Resident flash array (bytes)	256 - 512 - 1024 M	512-1024-2048-HD

Disk drive		
CD ROM	-	1 (option)
HDD (byte)*	-	>40 G

Interfaces		
Standard serial port	RS232	3xRS232
Parallel port	Bidirectional	
USB port	v. 1.1	3x v. 2.0
Mouse PS/2 port	1	1 + adapter
Keyboard PS/2 port	1	
CardBus slots (for Compact Flash)	1	-
PCI slots	1	
Video CRT out	-	1

Networks		
Integrated (in all models)	Ethernet 10/100 Mbit - RJ45	

Dimensions			
External (W x H x D) (mm)	336,3x256x93	336,3x256x93	425x300x126.5
Cut-out (W x H) (mm)	314x240	314x240	399x274

Clock		
Hardware clock	With battery	

Technical data		
Power supply	18...32 Vdc	
Power consumed (24 Vdc)	~ 25 W	~ 80 W
Protection level	IP 65 front	
Operating temperature (°C)	0...+50	
Storage/transport temperature (°C)	-20...+65	
Humidity (non condensing)	85%	
Weight (kg)	~ 5,4	~ 7,5
Certificates of approval	CE, c/UL/US in progress	

Installed Software		
Operating System	Microsoft® Windows® XP Embedded English	Microsoft® Windows® XP Embedded English Microsoft® Windows® XP Pro SP2 English

\* alternative to Flash Array